WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

B65D 71/00, 21/02

A1

(11) International Publication Number: WO 98/07636

(43) International Publication Date: 26 February 1998 (26.02.98)

SE

(21) International Application Number: PCT/SE97/01211

(22) International Filing Date: 4 July 1997 (04.07.97)

(71) Applicant (for all designated States except US): PERSTORP

21 August 1996 (21.08.96)

(71) Applicant (for all designated States except US): PERSTORP AB [SE/SE]; S-284 80 Perstorp (SE).

(72) Inventor; and
 (75) Inventor/Applicant (for US only): KRISTOFFERSSON, Karl-Gustaf [SE/SE]; Ekliden 9, S-286 36 Örkelljunga (SE).

(74) Agent: STENBERG, Yngve; Perstorp AB, S-284 80 Perstorp (SE).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published


With international search report.

(54) Title: TRAY FOR BOTTLES

(57) Abstract

(30) Priority Data: 9603020-0

Tray (1) for bottles (10) of polymeric material. The upper side of the tray (1) is provided with a number of receiving means (2) for the reception of the lower parts of the bottles (10). A number of parting and orienting tower-like protrusions (3) are placed between the receiving means (2). The protrusions (3) are provided with a number of resilient legs (4) forming an integrated part of the tray (1). The legs (4) extend upwards forming the sides of the protrusions (3). The legs (4) are provided with mainly vertical ribs (6) directed mainly towards the centre of the bottles (10). The legs (4) are pressing towards the lower parts of the bottles (10) so that the bottles (10) will be held in position during transport.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albenia	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	F	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijas	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbedos	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guines	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Paso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	(E	Ireland	'MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ.	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger-	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlanda	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzatan	NO	Norway	zw	Zimbebwe
. CF	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	'RU	Russian Federation		
DE	Germany	L	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
23	Estonia	LR	Liberia .	SG	Singapore		

WO 98/07636 PCT/SE97/01211

Tray for bottles

The present invention relates to a tray for bottles.

Transport packages such as crates for one-way or returnable bottles are quite common nowadays. These are usually designed so that they protect the bottles from thrusts and strikes since the bottles most often have been manufactured of glass. One advantage with these types of packages is that they have a very good stability towards the swaying that such packages will be exposed to during transport. One disadvantage is that these packages are very volume demanding during transport and storage when empty.

One type of bottle that has become more common during the recent years is the one-way and returnable bottle made from polymeric materials. These bottles are not nearly as sensitive to thrusts and strikes as glass bottles and do therefore not need a protecting package. They can also be used for carrying the load of packages placed above since they are insensitive to thrusts, whereby the height of the package can be made lower than the height of the bottle.

This type of transport packages, normally called trays, will give considerable advantages when transported and stored empty, since the height of the tray can be made considerably lower than bottle crates. Trays do further allow a somewhat higher amount of bottles per area unit than the bottle crate. The amount of material needed per carried bottle for the manufacturing of a bottle tray is also considerably lower then the corresponding amount of material in a bottle crate.

A disadvantage with bottle trays is however the relatively poor stability towards swaying of a stack of such trays containing bottles. A stack of trays containing bottles can easily overturn as each individual bottle tilts at strong breaking or at high corner speeds. This might cause hundreds of bottles to fall to the ground. This might be solved by providing the tray with upwards or downwards directed supports which would enhance the stability. This would however cause the tray to be more volume demanding when transported and stored empty. Thereby a good quality would be lost. The stability can also be increased by securing the stack with stretch foil, tensional strapping or other similar load-securing devices. This would however cause an unwanted increase in material used. The time consumed when stacking and de-stacking the bottles and the trays would also increase. Additionally the amount of unwanted waste is increased.

Yet another disadvantage with bottle trays is that bottles in the tray can bounce out of the top tray during shaky transports. It can also in certain cases be desirable that labels of the bottles are directed in the same direction for the best presentation of the goods. This is however impossible at the existing

types of trays since even very small vibrations will bring the bottles to rotate randomly.

It has, according to the present invention, been possible to solve the problems and drawbacks and a bottle tray where the bottles stand firmly has been achieved. The invention relates to a tray for bottles, preferably different types of re-usable and one-way bottles of polymeric material such as polyvinylchloride and polyalkyleneterephthalates. The bottles are provided with a bottom member and a side member. The upper side of the tray is provided with a number of receiving means for the reception of the lower parts of the bottles. A number of parting and orienting tower-like protrusions are placed between the receiving means. The invention is characterised in that the protrusions are provided with a number of resilient legs forming an integrated part of the tray by being connected to the tray or the protrusions via a leg base. The legs extend upwards forming the sides of the protrusions. The legs are further provided with mainly vertical ribs directed mainly towards the centre of the bottles. The legs are pressing towards the lower parts of the bottles so that the bottles will be held in position. It is hereby prevented that the bottles rotate, or that they bounce out of the tray during transport. All receiving means in the tray are preferably provided with legs with ribs placed at the protrusions.

The ribs placed on the legs are preferably provided with an undercut so that a circle A' touching the ribs placed around a receiving means at a height H' above the upper bottom surface of the tray is smaller than a circle A" touching the same ribs at a lower height H" above the upper bottom surface of the tray.

The tray is preferably manufactured through injection moulding of a thermoplastic material such as polyethylene, polypropylene, polybutene, polyamide, acrylonitrile-butadiene-styrenecopolymer, polyvinylchloride or the like.

The invention is explained further together with the enclosed drawings showing two embodiments of the invention wherein.

- -figure 1 shows schematically a part of a tray for bottles.
- -figure 2 shows schematically a second embodiment of a tray.
- -figure 3 shows schematically and in cross-section a receiving means.
- -figure 4 shows different embodiments of existing bottles.

WO 98/07636 3 PCT/SE97/01211

Figure 1 shows schematically a part of a tray 1 for one-way and returnable bottles 10 made from polymeric material. The upper side of the tray 1 is provided with a number of receiving means 2 for the reception of the lower parts of the bottles 10. A number of separating and orienting tower-like protrusions 3 are placed between the receiving means 2. The protrusions 3 are provided with a number of resilient legs 4 which press towards the lower parts of the bottles 10 so that the bottles 10 are held in position. Rotation and bouncing of the bottles 10 in the tray 1 during transport are hereby prevented.

Figure 2 shows schematically a part of a second embodiment of a tray 1 with receiving means 2 between which a number of separating and orienting protrusions 3 are placed. The protrusions 3 are provided with a number of resilient legs 4 which are connected to the protrusions 3 via a leg base 5. The legs 4 extend upwards along the sides of the protrusions 3. The legs 4 are further provided with vertical ribs 6 directed towards the centre of the bottles 10. The ribs 6 placed on the legs 4 are provided with an undercut so that a circle A' touching the ribs 6, placed around a receiving means 2, at a height H' above the upper bottom surface of the tray 1 is smaller than a circle A'' touching the same ribs 6 at a lower height H'' above the upper bottom surface of the tray 1.

Figure 3 shows schematically a receiving means 2 with surrounding protrusions 3 in cross-section. The protrusions are provided with a number of resilient legs 4 which are connected to the protrusions 3 via a leg base 5. The legs extend upwards along the sides of the protrusions 3. The legs 4 are further provided with vertical ribs 6 directed towards the centre of the bottles 10.

Figure 4 shows different existing types of re-usable and one-way bottles 10 of polymeric material. The bottles are provided with a bottom member 12 and a side member 13. Bottles with a protruding bottom member 12 are most suitable for use together with the invention since a snap-lock is achieved. However also bottles 10 without such a protruding bottom member 12 can advantageously be used together with the invention.


The invention is not limited to the embodiments shown since they can be varied within the scope of the invention. The legs can, per example in their free end be provided with a bellow-like spring. A greater holding force is hereby achieved.


Claims


- 1 Tray (1) for bottles (10), preferably different types of re-usable and one-way bottles of polymeric material such as polyvinylchloride and polyalkylene-terephthalates wherein the bottles (10) are provided with a bottom member (12) and a side member (13), the upper side of the tray (1) is provided with a number of receiving means (2) for the reception of the lower parts of the bottles (10), and a number of parting and orienting tower-like protrusions (3) are placed between the receiving means (2), c h a r a c t e r i s e d in that the protrusions (3) are provided with a number of resilient legs (4) forming an integrated part of the tray (1) by being connected to the tray (1) or the protrusions (3) via a leg base (5) wherein the legs (4) extend upwards forming the sides of the protrusions (3), that the legs (4) are provided with mainly vertical ribs (6) directed mainly towards the centre of the bottles (10) and that the legs (4) are pressing towards the lower parts of the bottles (10) so that the bottles (10) will be held in position whereby it is prevented that the bottles (10) rotate, or that they (10) bounce out of the tray (1) during transport.
- 2. Tray (1) according to claim 1 c h a r a c t e r i s e d in that the ribs (6) placed on the legs (4) are provided with an undercut so that a circle A' touching the ribs (6) placed around a receiving means (2) at a height H' above the upper bottom surface of the tray (1) is smaller than a circle A' touching the same ribs (6) at a lower height H' above the upper bottom surface of the tray (1).
- 3. Tray (1) according to claim 1 or 2 c h a r a c t e r i s e d in that all receiving means (2) in the tray (1) are provided with legs (4) with ribs (6) placed at the protrusions (3).
- 4. Tray (1) according to any of the claims 1 3 characterised in that the tray is manufactured through injection moulding of a thermoplastic material such as polyethylene, polypropylene, polybutene, polyamide, acrylonitrile-butadiene-styrenecopolymer, polyvinylchloride or the like.


<u>Fig.1</u>

1/3









INTERNATIONAL SEARCH REPORT

International application No. PCT/SE 97/01211

A. CLASSIFICATION OF SUBJECT MATTER								
IPC6: B65D 71/00, B65D 21/02 According to International Patent Classification (IPC) or to both national classification and IPC								
	B. FIELDS SEARCHED							
Minimum d	ocumentation searched (classification system followed by	y classification symbols)						
IPC6:	B65D							
Documenta	tion rearched other than minimum documentation to the	extent that such documents are included in	the fields searched					
SE,DK,FI,NO classes as above								
Electronic d	lata base consulted during the international search (name	of data base and, where practicable, search	i terms used)					
EPODOC		•						
C. DOCL	MENTS CONSIDERED TO BE RELEVANT		-					
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.					
A	US 5263605 A (CATON), 23 November figures 8,9, abstract	er 1993 (23.11.93),	1-4					
A	== == == == == == == == == == == == ==	W. 1405)	,					
A	EP 0099827 A1 (SAINT-GOBAIN EMB/ 1 February 1984 (01.02.84), abstract		1					
A	WO 9612657 A1 (DYNOPLAST A/S), 2 (02.05.96), abstract	2 May 1996	1					
A	WO 9407758 A1 (DYNOPLAST AS), 14 (14.04.94), abstract	April 1994	1.					
	. 							
Furth	er documents are listed in the continuation of Box	C. See patent family annex	.					
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of precipite or theory underlying the invention.								
"E" criter document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of amother citation or other "I document which may throw doubts on priority claim(s) or which is cited to establish the publication date of amother citation or other								
or docume means	reason (as specified) ant referring to an oral disclosure, use, exhibition or other	"Y" document of particular relevance the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination						
"P" document published prior to the international filing date but later than the priority date claimed being obvious to a person skilled in the art document member of the same patent family								
Date of the actual completion of the international search Date of mailing of the international search report								
		30 -10- 19	97					
	ober 1997	Authorized officer						
Name and mailing address of the ISA/ Swedish Patent Office Authorized officer								
Box 5055, S-102 42 STOCKHOLM Kerstin Brinkman								
Facsimile No. + 46 8 666 02 86 Telephone No. + 46 8 782 25 00								

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International application No.

01/10/97

PCT/SE 97/01211

	atent document in search repor	ι.	Publication date		Patent family member(s)		Publication date
US	5263605	A	23/11/93	CA DE EP ES FR RU WO	2072137 69004099 0497868 2094759 2653755 2057052 9106487	D,T A,B T A,B C	27/04/91 11/05/94 12/08/92 01/02/97 03/05/91 27/03/96 16/05/91
EP	0099827	A1	01/02/84	FR	2530226	A,B	20/01/84
WO	9612657	A1	02/05/96	EP FI NO NO	0784577 971452 179636 943972	A B	23/07/97 08/04/97 12/08/96 22/04/96
WO.	9407758	A1	14/04/94	CA EP FI FI NO	2145752 0662915 94044 924377 951183 308225	A B A A	14/04/94 19/07/95 31/03/95 30/03/94 28/03/95 24/07/95

This Page Blank (uspto)

AL AMK PAGE

BLANK PAGE